Grooving Machine KFU 1000 E



ref.no.: 951101

EAN: 4032689049823

Technical data

Nominal input	900 W
Nominal no-load speed	8000 - 15000 1/min
Cutting tool Ø	120 mm
Cutting depth	0 - 4,5 mm
Weight	4,9 kg
Universal-motor	230 V / 50 Hz

Delivery specification

1 Grooving-cutting blade, TCT, elliptical, 120 x 3.6 x 20 mm (4 3/4 x 1/8 x 13/16 in.), 12 teeth; Ref. No. 091794
1 Carrying case; Ref. No. 095034
1 Allen key WAF 4; Ref. No. 093074
1 Mains cable (32.8 ft); Ref. No. 087604

- Cutting grooves
- Compatible materials include resilient floor coverings

advantage for usage

- With level compensation - for constant cutting depth.
- With three rollers - to prevent tipping on uneven floors.

description

The unique feature of the KFU 1000 E is the built-in cutting blade lock for fast tool changes.

The 4.9 kg (10.8 lbs) weight and the 10 m (32.8 ft) mains cable give the KFU 1000 E freedom of movement and a large operating radius.

The powerful 900 watt (1.2 hp) single-phase motor allows a speed of 8000 - 1500 rpm and an accordingly clean cutting result. With the stepless electronic controls, you can use the machine for all types of material. Simply set the right speed and off you go!

Smallest possible wall distance: only 11.5 mm (7/16 in.).

If you prefer to work upright, we offer an exclusive additional handle as an optional accessory.

Accessories / Tools



Groove-cutting blade
elliptical, TCT, 120 x 3.6 x 20 mm (4 3/4 x 1/8 x 13/16 in.), 12 teeth



Groove-cutting blade
elliptical, TCT, 120 x 4.2 x 20 mm (4 3/4 x 3/16 x 13/16 in.), 12 teeth



Guide roller
R 1,5



Hand grooving tool
semicircular, with 5 replacement knives



Replacement knives
for hand grooving tool, semicircular



Additional handle, long

contact

MAFELL AG

Beffendorfer Straße 4
D-78727 Oberndorf / Neckar
Germany

Tel.: +49 7423 / 812-114
Fax: +49 7423 812-102
Email: export@mafell.de