MF 26 cc / 400 in carrying case

ref.no.: 917804

EAN: 4032689184043



Technical data

Cutting depth	0 - 26 mm
Nominal no-load speed	3600 - 6250 1/min
Cutting speed	39,9 m/s
Universal-motor	230 V / 50 Hz
Nominal input	1400 W
Weight	6,6 kg

Delivery specification

1 guide track 400

1 expanding groove cutter MF-VN 25
1 Parallel guide fence

1 Mains cable 4 m (13.1 ft)

examples for usage







The MF 26 cc / 400 is permanently attached to guide 400, so that the multi-cutter and the rail form an integral unit.



Stops are provided on the underside of the rail for adjusting the angle according to the scale. Once the machining operation has been performed, a spring automatically returns the multi-cutter to the starting position.

- Lengthwise and crosswise grooves
- V-grooves
- For routing wallboard prior to folding, bending techniques
- Routing and folding techniques with aluminum composite panels, sawing.
-

advantage for usage

- Turn the adjusting screw to set the cutting depth on the sliding scale with an accuracy of 1/10 mm.
- The glider slides on the surface of the workpiece and thus prevents tilting. It helps to hold the MF 26 cc securely in position when it is mounted on the guide rail as well.
- The guard opens with a single action. When it is opened, the starting lockout and sawblade lock engage automatically.
- With or without a rail – simply turn the pointer to show the exact cutting depth.

description

The design of the MF 26 cc is characterized by the use of extremely rugged, high-quality and precision-made parts, including the lightweight magnesium die-cast housing and impact-resistant, fiber glass-reinforced plastic components.

The MF 26 cc multi-cutter can be operated to a cutting depth of 26 mm on the guide rail and as a plunge-cut saw.

Whether sawing, routing or cutting grooves, genuine precision is best achieved with the aid of the guide rail system F.

Continuously variable speed up to 6250 rpm. For shaping, sawing and slotting an abundance of different materials.

Accessories / Tools



TCT saw blade
120 x 1.2/1.8 x 20 mm (4 3/4 in.)/ FT/TT 40 teeth, for fine sawing



TCT saw blade
120 x 1.2/1.8 x 20 mm (4 3/4 in.)/ AT, 12 teeth, for ripping



Guide track 770
max. tilt range 770 mm



Guide rail F 80
0,8 m (2,6 ft) long



Guide rail F 110
1.1 m (3.6 ft) long



Guide rail F 160
1.6 m (5.2 ft) long



Guide rail F 210
2,1 m (6,9 ft) long



Guide rail F 310
3,1 m (10,2 ft) long



Connecting piece F-VS
for joining two guide rails



Angle fence F-WA



Guide pocket set
F 80 + F 160 + F-WA + F-VS + 2 x F-SZ + 1 guide pocket



End cap F-EK
2 pieces



Splinter guard F-SS 3,4M
3.4 m (11.2 ft.) long



TCT saw blade
120 x 1.2/1.8 x 20 mm (4 3/4 in.)/ AT, 24 teeth, for universal use



TCT saw blade
120 x 1,2/1,8 x 20 mm / 40 trapezoidal teeth , for laminate

Suction hose LW 35 – 4 m long, anti-static (13.1 ft)



Guide fence F-RS

Expanding groove cutter MF-VN 25
Cutting width 15.4 - 25 mm

Aluminum composite cutter MF-AF 90
for 90° V-grooves up to 8 mm deep

Wallboard cutter MF-GF 90
for 90° V-grooves up to 12.5 mm deep

Slotting head MF-SE 3
for cutting 3 slots up to 26 mm

Roller edge guide MF-UA



Guide pocket F 160
for guide rails up to 1,6 m



Guide pocket set
F 80 + F 160 + F-WA + F-VS + 2 x F-SZ 100MM + Guide pocket



Non-slip profile F-HP 6,8 M
6.8 m (22.3 ft.) long



Screw clamp F-SZ 100MM
2 pieces, for fixing guide rail to workpiece

contact

MAFELL AG

Beffendorfer Straße 4
D-78727 Oberndorf / Neckar
Germany

Tel.: +49 7423 / 812-114
Fax: +49 7423 812-102
Email: export@mafell.de